

1) CONSTRUCTION: NOM. DIA.
 CONDUCTOR: 16 AWG 19/.0117 STRANDED TINNED COPPER .057"
 INSULATION: POLYVINYLCHLORIDE, .016" NOM. WALL THICKNESS .089"
 CABLE: (7) COLOR CODED SINGLES TWISTED TOGETHER AND WRAPPED WITH .270"
 A CLEAR POLYESTER BINDER TO FORM A CABLE CORE
 RIPCORD: INCLUDED UNDER JACKET FOR STRIPPING
 JACKET: POLYVINYLCHLORIDE, CHROME GRAY, .032" NOM. WALL THICKNESS. .334"
 OVER ALL CABLE DIAMETER

2) PHYSICAL PROPERTIES:
 TEMPERATURE RATING, MAX. 105°C
 TEMPERATURE RATING, MIN. -20°C
 WT./M', NOM., NET. 91.1 LBS.
 JACKET IS SUNLIGHT RESISTANT

3) ELECTRICAL CHARACTERISTICS:
 CAPACITANCE, MUTUAL, NOM. 26 PF/FT.
 DIELECTRIC WITHSTANDING, MIN. 1500V RMS
 VOLTAGE RATING, MAX. 600V
 D.C. RESISTANCE, MAX. PER ASTM B286 4.82 Ω/1000'


4) AGENCY APPROVALS:
 UL AWM STYLE 2586 105C 600V
 CSA AWM FT4

5) APPLICATION:
 INDUSTRIAL CONTROLS, MEDICAL ELECTRONICS AND OTHER APPLICATIONS WHERE A COMPACT 600V RATED CABLE IS REQUIRED. RoHS COMPLIANT MATERIALS.

6) PRINT:
 600V-TROL® E69976 **RU** AWM 2586 VW-1 -- CSA LL51726 AWM I/II A/B 105C 600V FT4 -- RoHS -- **(LOT DESIGNATOR)**

7) COLOR CODE:
 1. BLACK
 2. BROWN
 3. RED
 4. ORANGE
 5. YELLOW
 6. GREEN
 7. BLUE

8) PACKAGING
 TO BE PACKAGED AS PER QWC'S
 STANDARD PACKAGING



Created 07/19/13	DRAWN: BMD 05/11/17	
REV. 02	CHECKED: GBM 05/12/17	
TITLE 600V-TROL® -- 7/C 16 AWG -- AWM 2586, CSA AWM FT4 CABLE		
QUABBIN P/N	0735	1 of 1

CUSTOMER APPROVAL:

DATE: