

CABLE TO CONNECTOR CROSS REFERENCE

Stewart Connector Recommendation	Quabbin Cable Series	Performance Category	Cable Shielded or Unshielded	Special Notes
940-SP-3088-031	9760	T-1/DS-1/xDSL	Unshielded	Oval - 2 pair (.031 inner OD) Must remove outer layer of insulation
940-SP-3088-OB	9719 & 9720	T-1/DS-1	Unshielded	Oval - 2 pair Must remove outer layer of insulation
940-SP-3088-OB	9722	T-1/DS-1	Shielded Pairs	Oval
940-SP-3088-OB	9732	T-1/DS-1	Shielded Pairs	Oval
940-SP-3088-OB	9738	T-1/DS-1	Shielded Pairs	Oval
940-SP-3088-OB	9770	T-1/DS-1	Shielded Pairs	Oval
SS-37200-028	96xx	Category 5	Shielded	2 pair (.170" Max OD) By Pi Tape
SS-37000-007	55xx	Category 5e	Unshielded	
SS-37000-007	9469 - 9489 - 9499	Category 5e	Unshielded	
SS-37200-028	29xx	Category 5e	Shielded	.210" Nom., .220" Max (By Pi Tape)
SS-39100-021	22xx	Category 6	Unshielded	
SS-39100-028	2954 - 2965	Category 6a	Unshielded	
SS-39200-011	2942 - 2953	Category 6a	Shielded	
SS-39100-039	2216 - 2230	Mini-6 28 AWG	Unshielded	
SS-39200-055	2231-2245	Mini-6a 28 AWG	Shielded	Includes Boot 39100-888
SS-39200-036	2246-2258	Category 6a	Shielded	DataMax Relaxed Cable