

1) CONSTRUCTION:

CONDUCTOR:	14 AWG 41/30 STRANDED TINNED COPPER	NOM. DIA.	.070"
INSULATION:	POLYVINYLCHLORIDE, .016" NOM. WALL THICKNESS		.102"
CABLE:	(4) COLOR CODED SINGLES TWISTED TOGETHER AND WRAPPED WITH A CLEAR POLYESTER BINDER TO FORM A CABLE CORE.		.250"
SHIELD:	AN OVERALL ALUMINUM POLYESTER FOIL SHIELD (FOIL IN, 100% COVERAGE) SHALL BE APPLIED OVER THE CABLE CORE AND SHALL INCLUDE A 14 AWG 41/30 STRANDED TINNED COPPER DRAIN WIRE IN CONTACT WITH THE METALIZED SURFACE.		.279"
RIPCORD:	INCLUDED UNDER JACKET FOR STRIPPING		
JACKET:	POLYVINYLCHLORIDE, CHROME GRAY, .032" NOM. WALL THICKNESS.		
	OVERALL CABLE DIAMETER		.343" (BY PI TAPE)

2) PHYSICAL PROPERTIES:

TEMPERATURE RATING, MAX.	105° C
TEMPERATURE RATING, MIN.	-20° C
WT./M', NOM., NET.	95.1 LBS.
JACKET IS UV RESISTANT	

3) ELECTRICAL CHARACTERISTICS:

CAPACITANCE, MUTUAL, NOM.	32 PF/FT.
CAPACITANCE, GROUNDED, NOM.	60 PF/FT.
DIELECTRIC WITHSTANDING, MIN.	2000V RMS
VOLTAGE RATING, MAX.	600V
D.C. RESISTANCE, MAX. PER ASTM B286	2.94 Ω/1,000'


4) AGENCY APPROVALS:

- UL AWM STYLE 2586 105C 600V
- CSA AWM FT4
- MEETS (UL) VW-1 FLAME TEST

5) APPLICATION:

INDUSTRIAL CONTROLS, MEDICAL ELECTRONICS AND OTHER APPLICATIONS WHERE A COMPACT 600V RATED CABLE IS REQUIRED. RoHS COMPLIANT MATERIALS.

6) PRINT:


600V-TROL® E69976  AWM 2586 VW-1
 -- CSA LL51726 AWM I/II A/B 105C 600V
 FT4 -- RoHS -- **(LOT DESIGNATOR)**


7) COLOR CODE:

1. BLACK
2. BROWN
3. RED
4. ORANGE

8) PACKAGING

TO BE PACKAGED AS PER QWC'S STANDARD PACKAGING



Created 10/28/08	DRAWN: SGH 04/26/21	
REV. 03	CHECKED: JFR 4/26/21	
TITLE		
600V-TROL® -- 4/C 14 AWG -- AWM 2586 VW-1, CSA AWM FT4 CABLE -- SHIELDED		
QUABBIN P/N	0843	1 of 1

CUSTOMER APPROVAL:

DATE: