

1) CONSTRUCTION:		NOM. DIA.
CONDUCTOR:	26 AWG 7/34 STRANDED TINNED COPPER	.019"
INSULATION:	HIGH DENSITY POLYETHYLENE, .009" NOM. WALL THICKNESS	.037"
PAIRS:	COLOR CODED SINGLES TWISTED INTO PAIRS	.074"
CABLE:	(2) TWISTED PAIRS TWISTED TOGETHER AND WRAPPED WITH A FOAM POLYOLEFIN TAPE (100% COVERAGE) TO FORM A CABLE CORE.	.120"
SHIELDS:	AN OVERALL SHIELD OF 38 AWG TINNED COPPER BRAID (75% MINIMUM COVERAGE), SHALL BE APPLIED OVER THE CABLE CORE. A SECOND SHIELD OF ALUMINIZED POLYESTER FOIL (FOIL IN, 100% COVERAGE) SHALL BE APPLIED OVER THE BRAID.	.142"
JACKET:	ZHFR POLYURETHANE, <b>(COLOR, PER CHART 1)</b> , .046" NOM. WALL THICKNESS (PRESSURE)	OVERALL CABLE DIAMETER .233" ± .010" (BY CALIPER)

2) PHYSICAL PROPERTIES:	
TEMPERATURE RATING, MAX.	75°C
TEMPERATURE RATING, MIN.	-40°C (MANUFACTURER'S RECOMMENDED)
TEMPERATURE RATING, MIN.	-20°C (PER UL 444 COLD BEND)
WT./M', NOM., NET.	28.5 LBS.
FLEX LIFE	1 MILLION CYCLE TEST (10X CABLE O.D., MINIMUM RADIUS) 10 MILLION CYCLE TEST (20X CABLE O.D., MINIMUM RADIUS)
JACKET SMOKE GENERATION PER ASTM E662, NOM.	Ds = 251 (FLAMING, @ 4 MINUTES) Ds = 16 (NON-FLAMING, @ 4 MINUTES)
JACKET OIL RESISTANCE (IRM 902 OIL, 7 DAYS @ 100°C)	
TENSILE STRENGTH RETENTION, NOM.	100%
ELONGATION RETENTION, NOM.	80%

CHART 1:

QUABBIN P/N	JACKET COLOR
5080	BLACK
5081	BLUE
5082	TEAL


- 3) ELECTRICAL CHARACTERISTICS:  
SEE PAGE 2
- 4) AGENCY APPROVALS:  
NEC (ETL) TYPE CMX  
CEC C(ETL) TYPE CMX  
EU CE MARK: MEETS EU DIRECTIVE 2011/65/EU (RoHS II)

5) APPLICATION:  
PASSES VW-1

6) PRINT: (WHITE INK ON BLACK JACKET, ALL OTHERS BLACK INK)  
QUABBIN DATAMAX EXTREME HIGH FLEX ZERO HALOGEN INDUSTRIAL ETHERNET/IP PATCH CORD CAT 5e SF/UTP P/N **(P/N PER CHART 1)** -- C(ETL)US TYPE CMX OIL RES I 2 PR 26 AWG 75C -- CE RoHS -- **(LOT DESIGNATOR) (SEQUENTIAL FOOTAGE)**

- 7) COLOR CODE:  
1. GREEN X WHITE/GREEN  
2. ORANGE X WHITE/ORANGE

8) PACKAGING:  
TO BE PACKAGED AS PER QWC'S STANDARD PACKAGING



Created 01/12/11	DRAWN: SGH 04/14/21	
REV. 04	CHECKED: ZRS 04/16/21	
TITLE 2PR. SF/UTP HIGH FLEX INDUSTRIAL ETHERNET/IP PATCH CORD -- CAT 5e		
DRAWING #		QWC0012
		1 of 2

CUSTOMER APPROVAL: \_\_\_\_\_ DATE: \_\_\_\_\_

3) ELECTRICAL CHARACTERISTICS:

POE COMPLIANT TO 68 METERS WHEN INSTALLED PER RECOMMENDATIONS IN TIA TSB-184  
 CABLE WILL MEET CAT 5e CHANNEL REQUIREMENTS TO 68 METER LENGTH  
 CAPACITANCE, MUTUAL, NOM. 13.5 PF/FT. AT 1 MHz  
 DIELECTRIC WITHSTANDING, MIN. 1500V RMS  
 VOLTAGE RATING, MAX. 300V  
 D.C. RESISTANCE, MAX. 42.6  $\Omega$ /1,000'

**NOTE:** TESTING FOR THE FOLLOWING IS CONDUCTED OFF THE REEL. (FOR 100m OF CABLE)

IMPEDANCE	100 $\pm$ 15 $\Omega$	1 – 100 MHz
IMPEDANCE, SMOOTHED	100 $\pm$ 10 $\Omega$	TYPICAL 5 – 100 MHz
RETURN LOSS	1 $\leq f <$ 10 MHz	20 + 6 LOG( <i>f</i> ) dB MIN*
	10 $\leq f <$ 20 MHz	26 dB MIN*
	20 $\leq f \leq$ 100 MHz	26 – 5 LOG( <i>f</i> /20) dB MIN*
NEXT	1 $\leq f \leq$ 100 MHz	35.3 – 15 LOG( <i>f</i> /100) dB MIN
ACRF	1 $\leq f \leq$ 100 MHz	23.8 – 20 LOG( <i>f</i> /100) dB MIN
INSERTION LOSS	1 $\leq f \leq$ 100 MHz	1.5[1.967 $\sqrt{f}$ + 0.023( <i>f</i> ) + 0.050/ $\sqrt{f}$ ] dB MAX
DELAY	1 $\leq f \leq$ 100 MHz	534 + 36/ $\sqrt{f}$ ns MAX
DELAY SKEW	1 $\leq f \leq$ 100 MHz	<25 ns
COUPLING ATTENUATION PER IEC 62153-4-9	30 $\leq f \leq$ 100 MHz	60 dB MINIMUM
VELOCITY OF PROPAGATION	68%	

\*PER ODVA VOLUME 2 ETHERNET/IP

Created 01/12/11	DRAWN: SGH 04/14/21	
REV. 04	CHECKED: ZRS 04/16/21	
TITLE 2PR. SF/UTP HIGH FLEX INDUSTRIAL ETHERNET/IP PATCH CORD -- CAT 5e		
DRAWING #		QWC0012
		2 of 2

CUSTOMER APPROVAL:

DATE: