

1) CONSTRUCTION:  
 CONDUCTOR: 22 AWG 7/30 STRANDED TINNED COPPER  
 INSULATION: POLYVINYLCHLORIDE, .010" NOM. WALL THICKNESS  
 CABLE: (15) INSULATED CONDUCTORS TWISTED TOGETHER TO FORM A CABLE CORE  
 JACKET: POLYVINYLCHLORIDE, CHROME GRAY, .032" NOM. WALL THICKNESS

NOM. DIA.  
 .030"  
 .050"  
 .234"  
 OVERALL CABLE DIAMETER .298"

2) PHYSICAL PROPERTIES:  
 TEMPERATURE RATING, MAX. 60°C & 80°C  
 WT./M', NOM., NET. 62.1 LBS.

3) ELECTRICAL CHARACTERISTICS:  
 CAPACITANCE, MUTUAL 28 PF/FT.  
 DIELECTRIC WITHSTANDING, MIN 1500V RMS  
 VOLTAGE RATING, MAX. 300V  
 D.C. RESISTANCE, MAX. 16.7 OHMS/M'


4) AGENCY APPROVALS:  
 (UL) NEC TYPE CM  
 CSA AWM FT4  
 UL STYLE 2464

5) APPLICATION:  
 RS232 COMPUTER INTERCONNECT, CONTROL AND SOUND CABLE. RoHS COMPLIANT MATERIALS.

6) PRINT:  
 QUABBIN 7165R (UL) TYPE CM 22 AWG OR AWM 2464 -- CSA LL51726 AWM I/II A/B 80C 300V FT4 -- RoHS --  
**(LOT DESIGNATOR)**

- 7) COLOR CODE:
1. BLACK
  2. RED
  3. WHITE
  4. GREEN
  5. ORANGE
  6. BLUE
  7. BROWN
  8. YELLOW
  9. VIOLET
  10. GRAY
  11. PINK
  12. TAN
  13. RED/GREEN
  14. RED/YELLOW
  15. RED/BLACK

8) PACKAGING:  
 TO BE PACKAGED AS PER QWC'S STANDARD PACKAGING



REVISION 04	DATE:	DRAWN S. ADDIE	05/29/98	
REVISED BY	<i>B. Duceyuski</i> 10/25/06	CHECKED J. RIVERNIDER	05/29/98	
CHECKED	<i>J. Rivernider</i> 10/25/06	CHECKED		
CHECKED		CUSTOMER APPROVAL:	DATE:	TITLE 15/C 22 AWG PVC/PVC CABLE --TYPE CM. STYLE 2464. CSA AWM FT4
				QUABBIN P/N 7165 1 OF 1